



PVC Welding cables 电焊机电缆 سلك اللحام

STANDARD: 245 IEC 81.82 GB5013.6-1997

APPLICATION: Suitable for various welding machines, wire-sending machines, connecting wires and grounding.
Secondary side wires of welding.

AMP	Specification of NO /mm ²	Construction of Core NO/mm	Thickness of sheath(mm)	Out Diameter		Conductor resistance at 20°C(Ω/KM)
				Min dia(mm)	Max dia(mm)	
	16	513/0.2	2.0	9.2	11.5	1.15
200AMP	25	798/0.2	2.0	10.5	13.0	0.758
300 AMP	35	1121/0.2	2.0	11.5	14.5	0.536
400 AMP	50	1596/0.2	2.0	13.5	17.0	0.379
500 AMP	70	2241/0.2	2.0	15.0	19.5	0.268
600 AMP	95	3040/0.2	2.0	17.2	22.0	0.198
	120	1702/0.3	2.0	19.0	24.0	0.161

PVC Welding cables(American standard) سلك اللحام

Size	Construction of Core NO/mm	Max dia(mm)	Size	Construction of Core NO/mm	Max dia(mm)
4#	420/0.25	11.4	1/0	1064/0.25	16.7
3#	532/0.25	11.2	2/0	1323/0.25	18.5
2#	665/0.25	14.0	3/0	1666/0.25	20.3
1#	836/0.25	15.2	4/0	2107/0.25	22.1

PVC/Steel Spool Package 100m



Normal Plastic Belt Package 100m/100yard

